

Helping Customers Innovate, Improve & Grow

Table 1. Electrical Performance

Parameter	Symbol	Min.	Typ	Max	Units
Nominal Frequency	F_{NOM}	1.536		150.000	MHz
Mode		Fundamental, 3rd Overtone			
Operating Temperature Range	T_{OP}	0/70, -10/70, -20/70, -40/85			°C
Stability Over T_{OP} ¹	F_{STAB}	±10		±100	ppm
Frequency Tolerance ²	F_{TOL}		±10		ppm
Load Capacitance	C_L	6		32	pF
Shunt Capacitance	C_o			5	pF
Drive Level			10	100	uW
Aging / 1st year (at 25 °C)	F_{AGE}			±5	ppm
Insulation Resistance		500			MOhm
Storage Temperature	T_{STO}	-40		90	°C
Equivalent Series Resistance					
Crystal Frequency	ESR				Ohm
1.536MHz-2.000MHz				500	
2.001MHz-2.456MHz				450	
2.457MHz-3.000MHz				350	
3.001MHz-4.000MHz				90	
4.001MHz-5.000MHz				70	
5.001MHz-8.000MHz				60	
8.001MHz-10.000MHz				30	
10.001MHz-50.000MHz, fundamental				25	
24.000MHz-150.000MHz, 3rd Overtone				40	

Notes:

1. Referenced to the Frequency at 25 °C.

2. Frequency measured at 25 °C ± 3 °C.

Product is compliant to RoHS directive and fully compatible with lead free assembly.



Package Drawing

